





## Pendant Linear Luminaires

CE EN 60598-2-2 IP 40



|                       |                             |
|-----------------------|-----------------------------|
| Code                  | VK212 150LED S              |
| Power (W)             | 28,5                        |
| Light Flux (lm)       | 3450                        |
| Light Source          | SMD LED                     |
| Color Temp            | SMD LED                     |
| Dimensions (W/L/H mm) | 65x1500x85                  |
| Cut Out (W/L/H mm)    | -                           |
| Weight (Kg)           | -                           |
| Housing               | Aluminium                   |
| Paint                 | Electrostatic Powder Coated |
| Balast                | Vde Approved Driver         |
| Diffuser              | Opal PMMA Diffuser          |
| Mounted               | Pendant                     |



| Code           | Power (W) | Light Flux (lm) | Light Source | Color Temp | Dimensions (W/L/H mm) | Cut Out (W/L/H mm) | Weight (Kg) |
|----------------|-----------|-----------------|--------------|------------|-----------------------|--------------------|-------------|
| VK212 100LED S | 19        | 2300            | SMD LED      | 3000-4000K | 65x1000x85            | -                  | -           |
| VK212 120LED S | 23        | 2750            | SMD LED      | 3000-4000K | 65x1200x85            | -                  | -           |
| VK212 150LED S | 28,5      | 3450            | SMD LED      | 3000-4000K | 65x1500x85            | -                  | -           |